



GENERAL NOTES:

TRILOCK-75ES: ONE DIRECTION ELECTRICALLY CONTROLLED
 TRILOCK-75ES2: TWO DIRECTIONS ELECTRICALLY CONTROLLED
 TRILOCK-75MS: MECHANICAL UNIT

LONGER ARMS AVAILABLE (17" SHOWN).
 OPTIONAL PLATFORM AND RAILING AVAILABLE.

ELECTRICAL NOTES:

- POWER SERVICE OPTIONS:
1. 24 VDC
 2. 110 VAC SINGLE PHASE
 3. 220 VAC SINGLE PHASE 50/60HZ
 4. 220 VAC DUAL PHASE 50/60HZ

15A MAINS SERVICE REQ'D

AUTHORIZATION, FIRE ALARM REQUIRES DRY CONTACT FROM ACCESS CONTROL.

CODED NOTES:

1. TOP COVER - STAINLESS STEEL
2. CABINET - STAINLESS STEEL
3. ACCESS DOOR - 304 STAINLESS STEEL
4. ARM - STAINLESS STEEL n1-1/4" 16GA. (3) TYP.
5. COVER LOCK.
6. HUB: ANODIZED ALUMINUM
7. CONCEALED HINGE

FLOOR PLAN
 SECTION A-A SCALE 0.1:1